QUICK-LOCK®

Ceiling systems

Saint-Gobain API BV

Newtonweg 1 3846 BJ Harderwijk The Netherlands

P.O. Box 1 3840 AA Harderwijk The Netherlands

T +31 (0)341 474600

F +31 (0)341 474626

E sales@api.nl

Chamber of Commerce 08015950 BTW NL004318894.B.01

Declaration of Performance no 0007-156E

Quick-Lock 24 Corro-Plus EF

- 1. Unique identification of product : Quick-Lock®
- 2. Identification of the construction product components: Quick-Lock 24/38 CORRO-PLUS EF
- 3. Intended use: Suspended ceiling substructure component for use internally in buildings.
- 4. Manufacturer: Saint-Gobain API BV Newtonweg 1 Harderwijk The Netherlands www.api.nl
- 5. Authorized representatives: n.a.
- 6. System of assessment and verification of performance:
 - 6.1. Loadbearing capacity: System 3
 - 6.2. Reaction to fire: Coil-coated steel system 3
 - 6.3. Durability: System 4
- 7. Harmonized standard covering the construction product:
 - EN 13964:2014 suspended ceilings:
 - 7.1. Loadbearing capacity: Tests carried out by NB0432 MPA Dortmund; NB1153 TNO Delft
 - **7.2.** Reaction to fire: Coil-coated steel Commission decision 2010/737/EC: Tests carried out by NB 0679 CSTB RA08-0251
 - 7.3. Durability: EN 13964 Table 8
- 8. European Technical Assessment: n.a.





QUICK-LOCK° Ceiling systems

9. Declared performances:

	7.1 Load bearing capacity						7.2	7.3 Durability
	Deflection	Span min/max mm	Admissible bending moment (Madm) Nm	Maximum bending moment (Mu) Nm	Bending stiffness (EI) Nm ²	Notified body	Reaction to fire	
QL 24/38 CORRO-PLUS EF	Class 1	1000 / 1250	27,0	38,7	1913	NB0432	Class A1	Class C-D*;

^{*} Suitability for specific Class D situations to be based on expert judgement (EN13964 tabel 8)

Tolerances and dimensions fulfil the requirements as specified in EN 13964 table 2.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performances point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for on behalf of the manufacturer:

J. van Eekhout Managing Director

Harderwijk NL 21-03-2017



